

PRODUCT DATA SHEET



Avery® MPI™ 1005 6”

issued: 05/06/2003

Introduction

Avery MPI 1005 6” is a gloss white premium quality self-adhesive cast vinyl, highly conformable and opaque. It is designed for the Idanit 162A inkjet printer providing excellent machine runnability.

Because of the film's excellent durability and conformability, Avery MPI 1005 6” is highly recommended for applications on rivets and corrugations and/or prolonged outdoor use.

The adhesive is designed to have a permanent adhesion, but allows clean removal at the end of the graphic life by just using a professional heatgun.

Description

Film : 53 micron gloss white cast vinyl
Adhesive : permanent, grey, acrylic based
Backingpaper : tissue back liner, 155 g/m²

Conversion

Avery MPI 1005 6” is specially developed for use on the Idanit 162Ad and Idanit Novo inkjet printer and has been officially approved by Idanit using BL and Magic inks.

To enhance colour and protect images against UV radiation and abrasion, Avery MPI 1005 3” is recommended to be protected using an overlamine or varnish.

In the event of the final graphic being used on corrugated vehicles or substrates, the use of a varnish is recommended.

Please note that overlamination of Avery MPI 1005 3” with DOL films will negatively influence the conformability of the total construction.

For recommended combinations of DOL films and media, please refer to "Technical Bulletin 5.3. Recommended combinations of Avery® Overlaminates and Avery® Digital Print Media".

Uses

- Vehicle graphics.
- Architectural
- Transportation and general signage markings
- All permanent applications requiring conformability.

Features

- Offers clean removal at the end of the graphic life.
- Full opacity.
- Excellent printability and handling on Idanit 162Ad and Idanit Novo
- Easy conversion because of dimensionally stable special backing
- Outstanding durability and outdoor performance.
- Excellent conformability to irregular substrates.
- Superior high gloss appearance.



www.averygraphics.com

Graphics Division
Rijndijk 86, P.O. Box 118
2394 ZG Hazerswoude – The Netherlands
Tel +31 71 3421500 – Fax +31 71 3421538

PRODUCT CHARACTERISTICS

Avery® MPI™ 1005 6''

Physical properties

Features	Test method ¹	Results
Caliper, facefilm	ISO 534	53 micron
Caliper, facefilm + adhesive	ISO 534	80 micron
Elongation	DIN 53455	> 100 %
Dimensional stability	DIN 30646	0.4 mm max.
Adhesion, initial	FINAT FTM-1, stainless steel	490 N/m
Adhesion, ultimate	FINAT FTM-1, stainless steel	700 N/m
Flammability		Self-extinguishing
Shelf life	Stored at 22° C/50-55 % RH	1 year
Durability, unprinted	Vertical exposure	7 years

Temperature range

Features	Results
Minimum application temperature:	+10 °C
Service temperature:	- 40 °C to + 80 °C

Important

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use. All technical data are subject to change.

Warranty

Avery® branded materials are manufactured under careful quality control and are warranted to be free from defect in material and workmanship. Any material shown to our satisfaction to be defective at the time of sale will be replaced without charge. Our aggregate liability to the purchaser shall in no circumstances exceed the cost of the defective materials supplied. No salesman, representative or agent is authorised to give any guarantee, warranty, or make any representation contrary to the foregoing.

All Avery® branded materials are sold subject to the above conditions, being part of our standard conditions of sale, a copy of which is available on request.

1) Test methods

More information about our test methods can be found on our website.

2) Durability

The durability is based on middle European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the marking. For instance, in the case of signs facing south; in areas of long high temperature exposure such as southern European countries; in industrially polluted areas or high altitudes, exterior performance will be decreased.



www.averygraphics.com

Graphics Division
Rijndijk 86, P.O. Box 118
2394 ZG Hazerswoude – The Netherlands
Tel +31 71 3421500 – Fax +31 71 3421538