

PRODUCT DATA SHEET



issued: 21/02/2006

Avery® MPI™ 2041 Transparent

Introduction

Avery MPI vinyl 2041 is a glossy, transparent, polymeric calendered self-adhesive vinyl. It is suitable for use on super wide format inkjet and airbrush printers using solvent ink.

Avery MPI 2041 is highly recommended for a wide range of applications on flat substrates which require clean and easy removal.

Description

Film : 80 micron gloss transparent calendered vinyl
Adhesive : clear removable, acrylic based
Backingpaper : two sides polyethylene coated kraft paper, 140 g/m²

Conversion

Avery MPI 2041 is a multi-purpose vinyl, developed for use on various super wide format printers using solvent inks.

In Avery Technical Bulletin 5.15, printer compatibility details of Avery MPI media are listed.

To enhance colour and protect images against UV radiation and abrasion, Avery MPI 2041 Transparent is recommended to be protected using an overlamine or varnish.

For recommended combinations of DOL films and media, please refer to "[Technical Bulletin 5.3. Recommended combinations of Avery® Overlaminates and Avery® Digital Print Media](#)".

Uses

A wide variety of applications, such as durable promotional and point of sale advertising, to flat or regular surfaces, requiring clean and easy removal.

- Vehicle graphics (flat and slightly curved surfaces).
- Interior & exterior signs.
- Window decoration.
- Promotional and point of sale advertising.

Features

- High transparency.
- Excellent printability and handling on selected printers.
- Excellent durability and outdoor performance.
- High gloss appearance.
- Easy and clean removal (up to 2 years).



www.averygraphics.com

Graphics Division
Rijndijk 86, P.O. Box 118
2394 ZG Hazerswoude – The Netherlands
Tel +31 71 3421500 – Fax +31 71 3421538

PRODUCT CHARACTERISTICS

Avery® MPI™ 2041 Transparent

Physical properties

| Features | Test method ¹ | Results |
|------------------------------|------------------------------|--------------------|
| Caliper, facefilm | ISO 534 | 80 micron |
| Caliper, facefilm + adhesive | ISO 534 | 105 micron |
| Elongation | DIN 53455 | > 100 % |
| Dimensional stability | DIN 30646 | 0.4 mm max. |
| Adhesion, initial | FINAT FTM-1, stainless steel | 240 N/m |
| Adhesion, ultimate | FINAT FTM-1, stainless steel | 300 N/m |
| Flammability | | Self-extinguishing |
| Shelf life | Stored at 22° C/50-55 % RH | 2 year |
| Durability, unprinted | Vertical exposure | 5 years |

Temperature range

| Features | Results |
|----------------------------------|--------------------|
| Minimum application temperature: | +10 °C |
| Service temperature: | - 40 °C to + 80 °C |

Important

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use. All technical data are subject to change.

Warranty

Avery® branded materials are manufactured under careful quality control and are warranted to be free from defect in material and workmanship. Any material shown to our satisfaction to be defective at the time of sale will be replaced without charge. Our aggregate liability to the purchaser shall in no circumstances exceed the cost of the defective materials supplied. No salesman, representative or agent is authorised to give any guarantee, warranty, or make any representation contrary to the foregoing.

All Avery® branded materials are sold subject to the above conditions, being part of our standard conditions of sale, a copy of which is available on request.

1) Test methods

More information about our test methods can be found on our website.

2) Durability

The durability is based on middle European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the marking. For instance, in the case of signs facing south; in areas of long high temperature exposure such as southern European countries; in industrially polluted areas or high altitudes, exterior performance will be decreased.



www.averygraphics.com

Graphics Division
Rijndijk 86, P.O. Box 118
2394 ZG Hazerswoude – The Netherlands
Tel +31 71 3421500 – Fax +31 71 3421538